

Low Broadband Antenna

90° 2.0 m x-polarized FET Antenna

Part Number: 7487.00	Horizontal Beamwidth: 90° Gain: 15dBi / 12.9dBd	Electrical Downtilt: 0° Connector Type: 7/16 DIN female
-------------------------	--	--

806-960 MHz

The Powerwave broadband dual polarized antenna is designed with a slant $\pm 45^\circ$ configuration having equal signal strengths on both polarizations. The design ensures the highest possible diversity gain, isolation and cross polarization discrimination. Its slim design and sophisticated electrical performance, typical of Powerwave antennas, ensures maximum efficiency as well as stable pattern over the entire frequency range. This design relies on leading-edge patch technology fed via a micro strip PCB network. Special attention has been paid to ensure antenna pattern peak performance, making this an excellent choice for optimal cell planning.



Key Benefits

- Excellent broad- and multi-band capabilities
- Polarization purity maximizes diversity gain
- Excellent pattern performance and high gain over frequency
- Guaranteed passive intermodulation performance
- Light, slim and robust design

ANTENNA
SYSTEMS

BASE STATION
SYSTEMS

COVERAGE
SYSTEMS


Low Broadband Antenna

806-960 MHz

Electrical Specifications

Frequency Range (MHz)	806 - 960
Polarization	Dual slant $\pm 45^\circ$
Gain (dBi) / (dBd)	15 / 12.9
Nominal Impedance (Ohm)	50
VSWR (824-960 MHz)	< 1.4:1
Isolation	> 30
Horizontal -3 dB beamwidth	90°
Vertical -3 dB beamwidth	10°
Electrical downtilt	0°
Front-to-back ratio, co-polar (dB)	>30
First upper sidelobe suppression (dB)	>21
Maximum input power (W)	600
IM, 3rd order, @2x43dBm (dBc)	<-150

All specifications are subject to change without notice.
Contact your Powerwave representative for complete performance data.



Typical Horizontal and Vertical 7487.00 Patterns

Mechanical Specifications

Connector Type	2 x 7/16 DIN female
Connector Position	Bottom
Dimensions, HxWxD	2080x280x125mm (8'8"x11"x5")
Weight Brackets	16 kg
Wind Load, Frontal, 42m/s Cd=1	642 N (144 lbf)
Survival Wind Speed	70m/s (156 mph)
Lightning Protection	DC grounded
Radome Material	GRP
Radome Color	Light Gray
Packing Size	2280x355x255mm (9'4"x1'2"x10")
Shipping Weight	17 kg

Corporate Headquarters
Powerwave Technologies, Inc.
1801 East St. Andrew Place
Santa Ana, CA 92705 USA
Tel: 714-466-1000
Fax: 714-466-5800
www.powerwave.com

Main European Office
Antennvägen 6
SE-187 80 Täby
Sweden
Tel: +46 8 540 822 00
Fax: +46 8 540 823 40

Main Asia Pacific Office
23 F Tai Yau Building
181 Johnston Road
Wanchai, Hong Kong
Tel: +852 2512 6123
Fax: +852 2575 4860



©Copyright September 2003, Powerwave Technologies, Inc. All Rights reserved. Powerwave, Powerwave Technologies, The Power in Wireless and the Powerwave logo are registered trademarks of Powerwave Technologies, Inc.

COVERAGE AND CAPACITY

TECHNOLOGY LEADERSHIP

GLOBAL PARTNER

INTEGRATED SOLUTIONS

QUALITY AND RELIABILITY